

MASTER.CF TCHR

```
smtp inet n - n - - smtpd
-o content_filter=amavisfeed:[127.0.0.1]:10024
amavisfeed unix - - n - 2 smtp
-o smtp_data_done_timeout=1200
-o smtp_send_xforward_command=yes
-o disable_dns_lookups=yes
-o max_use=20
127.0.0.1:10025 inet n - n - - smtpd
-o content_filter=
-o local_recipient_maps=
-o smtpd_helo_restrictions=
-o smtpd_client_restrictions=
-o smtpd_sender_restrictions=
-o smtpd_sasl_auth_enable=yes
-o smtpd_recipient_restrictions=permit_mynetworks,reject
-o mynetworks=127.0.0.0/8
# -o smtpd_error_sleep_time=0
-o smtpd_soft_error_limit=1001
-o smtpd_hard_error_limit=1000
-o receive_override_options=no_header_checks,no_unknown_recipients_checks
-o local_header_rewrite_clients=

587 inet n - n - - smtpd

#submission inet n - n - - smtpd
# -o smtpd_enforce_tls=yes
# -o smtpd_sasl_auth_enable=yes
# -o smtpd_client_restrictions=permit_sasl_authenticated,reject
# testy 20.11.2009
smtps inet n - - - - smtpd -v
-o smtpd_tls_wrappermode=yes
-o smtpd_sasl_auth_enable=yes
-o smtpd_client_restrictions=permit_sasl_authenticated,reject
```

MAIN.CF TCHR

```
smtpd_helo_restrictions =
#####
# wywala niektore hosty na windzie przed forti #
# reject_unknown_helo_hostname, #
# reject_non_fqdn_helo_hostname, #
#####
reject_unauth_pipelining,
reject_invalid_helo_hostname,
permit

smtpd_client_restrictions =
reject_unknown_reverse_client_hostname,
reject_rbl_client chikor.rbl.tld,
# reject_rbl_client bl.spamcop.net,
reject_unauth_pipelining,
permit

smtpd_recipient_restrictions = permit_sasl_authenticated,
permit_mynetworks,
check_helo_access hash:/etc/postfix/helo_checks,
check_helo_access pcre:/etc/postfix/helo_checks.pcre,
reject_unknown_helo_hostname,
reject_non_fqdn_helo_hostname,
reject_unauth_destination,
reject_non_fqdn_recipient,
reject_unknown_recipient_domain,
reject_unlisted_recipient,
reject_sender_login_mismatch,
check_policy_service unix:postgrey/socket

smtpd_data_restrictions =
reject_unauth_pipelining,
reject_multi_recipient_bounce,
permit

smtpd_sender_restrictions =
check_sender_access hash:/etc/postfix/access,
# reject_sender_login_mismatch,
# 13.11.2009 wyłączone unknown_sender bo byc moze problem z revDNS dla TCHR
# reject_unknown_sender_domain,
reject_non_fqdn_sender,
permit
```

MASTER.CF HLOND

```
smtp inet n - n - - smtpd

#submission inet n - n - - smtpd
# -o smtpd_enforce_tls=yes

# UWAGA ponizsze 2 linie nie dzialaja - odrzucaja polaczenia - dziwne do sprawdzenia

# -o smtpd_sasl_auth_enable=yes
# -o smtpd_client_restrictions=permit_sasl_authenticated,reject

587 inet n - - - - smtpd

#smtps inet n - n - - smtpd
# -o smtpd_tls_wrappermode=yes
# -o smtpd_sasl_auth_enable=yes
# -o smtpd_client_restrictions=permit_sasl_authenticated,reject
```

MAIN.CF HLOND

```
smtpd_client_restrictions =
# - uwalamy upierdliwych klientow, ktorzy nie maja kultruy osobistej lub spamuja - reczne aktualizacje
check_client_access hash:/etc/postfix/access_recipients,
reject_rbl_client chikor.rbl.tld,
# reject_rbl_client bl.spamcop.net,
reject_unauth_pipelining,
reject_non_fqdn_recipient,
permit

smtpd_sender_restrictions =
check_sender_access hash:/etc/postfix/access_recipients
# - nie dziala - reject_sender_login_mismatch
reject_unknown_sender_domain
reject_rbl_client chikor.rbl.tld,
# reject_rbl_client bl.spamcop.net,
reject_non_fqdn_sender
permit

smtpd_recipient_restrictions =
permit_sasl_authenticated
permit_mynetworks
reject_unauth_destination
reject_non_fqdn_recipient
reject_unlisted_recipient
reject_unknown_recipient_domain
reject_unknown_helo_hostname
check_sender_access hash:/etc/postfix/access
# - warn daje opcje przetestowania, przepuszcza mail ale powiadamia admina ze powinien byc REJECT
# - warn_if_reject
# - nie dziala oddawanie zwrotek bez pluginu - reject_unsigned_bounce
reject_sender_login_mismatch
check_policy_service unix:postgrey/socket

smtpd_data_restrictions =
reject_unauth_pipelining
reject_multi_recipient_bounce
permit
```